






WYREFLEX

WYREFLEX NEOPRENE COATED DUCTING



Product Information

Order Ref:	WYR-SIZE MM
Tube:	DOUBLE PLY, NEOPRENE COATED POLYESTER FABRIC FLEXIBLE DUCTING WITH TWIN STEEL WIRE HELIX. EXTREMELY FLEXIBLE, ALLOWS A TIGHT BEND RADIUS. LINED WITH EPDM
Cover:	BLACK WITH YELLOW IDENTIFICATION STRIPE
Application:	SUITABLE FOR SUCTION AND CONVEYANCE OF AIR, FUMES AND GASES, DUST COLLECTION AND LIGHT MATERIALS HANDLING

	 ID	 WP	 VACUUM	 BR	 W/A	 coil
Inch	mm	BAR	m.H ² O	mm	kg/m	m
1	25	0.70	0.35	45	0.30	4
1 1/4	32	0.70	0.30	45	0.40	4
1 1/2	38	0.70	0.30	45	0.40	4
1 3/4	44	0.65	0.30	60	0.40	4
2	51	0.65	0.25	60	0.50	4
	57	0.60	0.20	70	0.60	4
2 1/2	64	0.60	0.20	70	0.70	4

	70	0.60	0.20	95	0.70	4
3	76	0.50	0.20	95	0.70	4
	83	0.50	0.20	110	0.90	4
	89	0.50	0.15	110	0.90	4
4	102	0.50	0.15	120	1.30	4
	114	0.45	0.10	120	1.50	4
5	127	0.45	0.10	145	1.70	4
	140	0.45	0.10	175	1.90	4
6	152	0.35	0.05	175	2.10	4
	178	0.35	0.05	220	2.40	4
8	203	0.30	0.05	240	3.20	4
	229	0.20	0.05	270	3.60	4
	254	0.20	0.05	290	4.40	4
	305	0.10	0.02	340	6.40	4



-55°C to +130°C

Branding: NONE
Colour : BLACK WITH YELLOW STRIPE