



Equal Tee Type FI-T ▪ Series LL / L / S



Ordering Codes

FI-T-10*L*-W3*-MS

* Equal Tee		FI-T
* Outside Tube Diameter D1 (in mm)		-10
* Series	Extra-Light Series	LL
	Light Series	L
	Heavy Series	S
* Material Code	Steel, zinc/nickel-plated	-W3
Please contact STAUFF for alternative materials and surface finishings.		
* Assembling / Kitting	Fitting body only	—
	Fitting body supplied with cutting rings and union nuts	-MS
	Fitting body supplied with soft-sealing cutting rings and union nuts	-MSV

Series	Tube OD	PN (bar/psi)	Dimensions					S1	S2	Weight (kg/lbs) ca. per 100 ²	Ordering Codes ³
	D1 (mm/in)		D2 (mm/in)	L	L1 ¹	L2					
LL	4	100	3	15	42	11	9	10	1,00	FI-T-04LL-W3	
	.16	1450	.12	.59	1.65	.43	.35	.39	2.20		
	6	100	4,5	15	42	9,5	9	12	1,23	FI-T-06LL-W3	
	.24	1450	.18	.59	1.65	.37	.35	.47	2.70		
	8	100	6	17	46	11,5	12	14	1,91	FI-T-08LL-W3	
L	.31	1450	.24	.67	1.81	.45	.47	.55	4.19		
	6	500	4	19	54	12	12	14	2,66	FI-T-06L-W3	
	.24	7250	.16	.75	2.13	.47	.47	.55	5.86		
	8	500	6	21	58	14	12	17	3,17	FI-T-08L-W3	
	.31	7250	.24	.83	2.28	.55	.47	.67	6.97		
	10	500	8	22	60	15	14	19	4,06	FI-T-10L-W3	
	.39	7250	.31	.87	2.36	.59	.55	.75	8.93		
	12	400	10	24	64	17	17	22	5,52	FI-T-12L-W3	
	.47	5800	.39	.94	2.52	.67	.67	.87	12.15		
	15	400	12	28	72	21	19	27	9,98	FI-T-15L-W3	
	.59	5800	.47	1.10	2.83	.83	.75	1.06	21.95		
	18	400	15	31	80	23,5	24	32	14,83	FI-T-18L-W3	
	.71	5800	.59	1.22	3.15	.93	.94	1.26	32.63		
	22	250	19	35	88	27,5	27	36	18,81	FI-T-22L-W3	
	.87	3625	.75	1.38	3.46	1.08	1.06	1.42	41.39		
	28	250	24	38	94	30,5	36	41	30,44	FI-T-28L-W3	
	1.10	3625	.94	1.50	3.70	1.20	1.42	1.61	66.97		
	35	250	30	45	112	34,5	41	50	49,27	FI-T-35L-W3	
	1.38	3625	1.18	1.77	4.41	1.36	1.61	1.97	108.39		
42	250	36	51	126	40	50	60	72,20	FI-T-42L-W3		
1.65	3625	1.42	2.01	4.96	1.57	1.97	2.36	158.84			
S	6	800	4	23	62	16	12	17	4,60	FI-T-06S-W3	
	.24	11600	.16	.91	2.44	.63	.47	.67	10.12		
	8	800	5	24	64	17	14	19	6,21	FI-T-08S-W3	
	.31	11600	.20	.94	2.52	.67	.55	.75	13.65		
	10	800	7	25	68	17,5	17	22	7,92	FI-T-10S-W3	
	.39	11600	.28	.98	2.68	.69	.67	.87	17.42		
	12	630	8	29	76	21,5	17	24	10,88	FI-T-12S-W3	
	.47	9135	.31	1.14	2.99	.85	.67	.94	23.93		
	14	630	10	30	80	22	19	27	12,97	FI-T-14S-W3	
	.55	9135	.39	1.18	3.15	.87	.75	1.06	28.53		
	16	630	12	33	86	24,5	24	30	10,97	FI-T-16S-W3	
	.63	9135	.47	1.30	3.39	.96	.94	1.18	24.14		
	20	400	16	37	96	26,5	27	36	25,58	FI-T-20S-W3	
	.79	5800	.63	1.46	3.78	1.04	1.06	1.42	56.28		
	25	400	20	42	108	30	36	46	44,75	FI-T-25S-W3	
	.98	5800	.79	1.65	4.25	1.18	1.42	1.81	98.46		
	30	400	25	49	124	35,5	41	50	68,20	FI-T-30S-W3	
1.18	5800	.98	1.93	4.88	1.40	1.61	1.97	150.04			
38	400	32	57	144	41	50	60	108,00	FI-T-38S-W3		
1.50	5800	1.26	2.24	5.67	1.61	1.97	2.36	237.60			

¹ Approximate dimension in assembled condition.

² Weight excluding cutting rings and union nuts.

³ Standard scope of delivery: Fitting body only.