Technical Data Sheet

Bondloc BPB – Pipe Repair Bandage Revised 03.08.10



Bondloc BPB Pipe Repair Bandage

PRODUCT DESCRIPTION

BPB Pipe Repair Bandage is a resin impregnated glass fibre-reinforced repair tape designed for the rapid repair of cracks and leaks. It is easy to use and repaired items can be back in use in less than 30 minutes.

APPLICATIONS

BPB Pipe Repair Bandage can be used on pipework in high pressure and high temperature situations. Steel and aluminium works, petroleum plants, power stations, manufacturing, pipe porosity and merchant shipping.

USEFUL HINTS

- Anti-corrosion, pipe protection Protect pipes from environmental corrosion
- Wear protection protects pipes and metal parts against abrasive wear.
- Concrete and Steel protection protect concrete pillars and steel structures from salt corrosion.

INSTRUCTIONS FOR USE

Clean mating surfaces for application. Note when grinding or wire brushing use a dust mask. Dust from cleaning threads may contain metal compounds. Inhalation may cause lung injury or other harm. Apply a thin coating to threads, flats, nuts and bolts. Assemble and wipe away any excess.

TECHNICAL FEATURES

Working Time	2-5 minutes
Cured material life	10-20 years dependent on
	repair quality, environmental
	conditions, pipe temperature
	etc.
Initial Cure Time	7-10 minutes
Functional Cure	30-45 minutes
Full cure	24 hours
Shore D Hardness	70
Max service	250°C
temperature	
Pressure resistance	30 bar
Chemical resistance	Acetone, ammonia, sulphuric acid (30%), ethyl alcohol, mineral spirits, gasoline, MEK, toluene, diesel, hydrochloric acid, varsol, ethylene glycol, crude oil, hydraulic oil (test period 40 days)

HEALTH & SAFETY IN USE

This technical information sheet for does not constitute a Material Safety Data Sheet (MSDS). Before using this product ensure you have read and fully understand the MSDS.

PRESENTATION

Pipe Bandage......50mm