Technical Data Sheet

Super Universal Tractor Oil 15w-30

Product Code: AGR014 - Revision: 20181112

Product Description

Designed to cover virtually all the lubrication requirements of agricultural machinery including farm tractors. It provides excellent high and low temperature stability, high standards of engine cleanliness and good oxidation resistance. Its natural high lubricity offers lower internal friction for reduced engine wear.

Benefits			Applications	
 Natural high lubricity. Good anti-foaming and air release properties. Excellent anti-wear Protection. Helps reduce wet brake noise. Suitable for most agricultural machinery requirements. 			Engine oil: Suitable for all four stroke, naturally aspirated and turbocharged diesel engines and four stroke petrol engines.	
			Hydraulic oil: Has good oxidation resistance, thermal stability and low temperature performance.	
			Transmission oil: Primarily formulated to be used in farm tractors and other plant where the transmission contains oil immersed "wet brake systems.	
Typical Test Data			Product Profile	
Density @ 15°C Flash Point (°C) Kinematic Viscosity cSt @ 100°C Kinematic Viscosity cSt @ 40°C Pour Point (°C) Viscosity Index		0.88 >190 11.5 79 <-35 137	ACEA API Allison Caterpillar Ford Massey Ferguson New Holland Mercedes Benz ZF	E3 GL-4, CG-4 C4 TO-2 M2C159 B/C M1139/ 1144/ 1145 82009202 228.1 06B, 06C, 06L, 07B, 07D

