

Technical Data Sheet



Semi Synthetic UTTO 10w-40

Product Code: AGR022 - Revision: 20181218

Product Description

Formulated from the premium quality semi-synthetic base oils, together with a special performance package and shear stable viscosity modifiers, providing an advanced lubricant which demonstrates excellent performance characteristics against the various stringent test requirements of major equipment manufacturers.

Benefits

- Superior oxidation stability.
- Outstanding rust and corrosion protection.
- Excellent wet brake, anti-squawk and chatter suppression.
- Exceptional anti-wear and extreme pressure properties.
- Excellent high and low temperature performance.
- Low foaming tendency and good seal compatibility.

Applications

Suitable for use in hydraulic – transmission fluid, specifically designed for use in agricultural tractor power transmission – hydraulic systems, inboard wet brakes and rear axles, employed in the majority of modern farm tractors, agricultural machinery and some construction equipment.

Typical Test Data

Density @ 15°C	-	0.87
Flash Point (°C)	-	>190
Kinematic Viscosity cSt @ 100°C	-	13.5
Kinematic Viscosity cSt @ 40°C	-	95
Pour Point (°C)	-	<-36
Viscosity Index	-	143

Product Profile

Allison	C4
API	GL-4
Case	MS1210
Caterpillar	TO-2
Ford	M2C86C, M2C134D
John Deere	J20C
Massey Ferguson	M1145, M1143
ZF	03E, 05F, 06B, 17E, 21F