

Milwaukee Power Tools (MILM18ONEIW5)

# M18 ONEIWF12-502X Fuel™ ONE-KEY™ /2in FR Impact Wrench 18V 2 x 5.0Ah

The Milwaukee M18 ONEIWF12 Fuel ONE-KEY Impact Wrench connects via Bluetooth with the Milwaukee ONE-KEY app. Allows for complete tool customisation, allowing you to tune the tool to your needs. Configure to any application choosing optimum tool settings for repeatable precision. Save up to 4 custom settings to the tool's memory for fast selection on the jobsite. Select from a range of application profiles or quickly create your own for perfect results on every trigger pull. ONE-KEY app also provides inventory function for total management of your complete tool/equipment fleet. Offers 4 modes of operation thanks to its unique Milwaukee DRIVE CONTROL, which allows the user to shift into four different speed and torque settings to maximise application versatility. The 4 modes are: -Mode 1: For precision work -Mode 2: Helps prevent damage to fasteners and material -Mode 3: Delivers maximum performance for the toughest applications -Mode 4: Intelligently detects when the tool has impacted on a fastener for one second automatically shutting the tool down, reducing overdriving and damaging materials Mode 4: No Load Speed: 0-2,000/min, Impact Rate: 0-2,600, Torque: 0-120Nm M18 ONEIWF12-502X: 2 x 18V 5.0Ah Li-Ion Batteries. M18 ONEIWF12-0: Bare Unit, No Battery or Charger Supplied. Specification Bit Holder: 1/2in Friction Ring No Load Speed: 0-1,700/0-2,000/0-2,500/min. Impact Rate: 0-2,400/0-2,600/0-3,100/bpm Torque : 40/120/300Nm The Milwaukee M18 ONEIWF12-502X Fuel ONE-KEY 1/2in FR Impact Wrench is supplied with: 2 x 18 Volt 5.0Ah Li-Ion Batteries, 1 x Charger and 1 x Heavy-Duty Case.



<b>Tool Holder</b>	<b>Voltage</b>	<b>Input Power (Battery)</b>	<b>No Load Speed RPM</b>
1/2in Friction Ring	18V	2 x 5.0Ah Li-Ion	0-1,700/0-2,000/0-2,500
<b>Impact Rate RPM</b>	<b>Max. Torque (Nm)</b>	-	-
0-2,400/0-2,600/0-3,100	300	-	-