

4SP HYDRAULIC HOSE GLOBAL FLEX



| Hose | | | Inside Ø | | Outside Ø | Working Pressure | | Burst Pressure | Bend Radius | Weight |
|-------------|-----------|----|----------|------|-----------|------------------|------|----------------|-------------|--------|
| part number | dash size | DN | inch | mm | mm | bar | psi | bar | mm | kg/m |
| GF4SP08 | -8 | 12 | 1/2 | 12.7 | 23.8 | 415 | 6020 | 1660 | 230 | 0.89 |
| GF4SP12 | -12 | 19 | 3/4 | 19.0 | 31.4 | 350 | 5075 | 1400 | 300 | 1.50 |
| GF4SP16 | -16 | 25 | 1 | 25.4 | 38.5 | 280 | 4060 | 1120 | 340 | 2.00 |

Recommended for

All high pressure hydraulic applications where a durable, flexible hose is required

Tube

Oil resistant synthetic rubber

Reinforcement

Four high tensile steel wire braids

Cover

Oil and weather resistant synthetic rubber

Temperature range

-40°C to +121°C

Standards

DIN EN 856 4SP

GLOBAL FLEX

GF4SP08 —DN12—1/2" 4SP —DIN EN856 WP 415 BAR/6020 PSI