


YB-P16HP

Global Flex Crimping Machine

PB-P16HP is a hand pumped operated hydraulic crimping machine, which is most suitable for repair workshops and feild use. They are easy to use, lightwieght and compact allowing them to be carried and/or stored to any location





GLOBAL FLEX

TECHNICAL DATA

Max crimping dia (mm)	10 - 45	
Max crimping dia (inches)	0.39 - 1.77	
Max crimping force (kN)	955	
Max crimping force (tonnage)	95	
Cycle time 10mm (s)	-	
Hose size ID (inches)	1	
Die set series	P16	
Max opening (mm)	+20	
Max opening without dies (mm)	59	
Master die D/L (inches)	1.54 / 2.52	
Motor power (kW/HP)	-	
Oil tank volume (L)	-	

P16 DIFS

LTQ DIE2				
DieSetNo	Crimping Range	ID (mm)	L (mm)	
P16/06*	6.0 - 8.0	6	55	
P16/08*	8.0 - 10.0	8	55	
P16/10*	10.0 - 12.0	10	55	
P16/12*	12.0 - 14.0	12	55	
P16/14	14.0 - 16.0	14	55	
P16/16	16.0 - 19.0	16	55	
P16/19	19.0 - 23.0	19	55	
P16/23	23.0 - 27.0	23	55	
P16/27	27.0 - 31.0	27	65	
P16/31	31.0 - 38.0	31	65	

*Non standard dies



Hydraulic Hose & Fittings

Looking for hydraulic hose and fittings to go with your new swaging machine? We stock large quantities of hydraulic hose and fittings for use across every industry including; 1 wire, 2 wire, 4 wire and 6 wire hose, and fittings available in mild or stainless steel.

Looking to start a mobile hose replacement business?

We have a recommended starting stock list for any new van, speak to our sales team to discuss your specific needs.

30+ Years in the Hydraulic Industry





