




# **Global Flex Crimping Machine**

P32CS hose crimping machine has been designed to crimp up to 2" diameter4-spiral hoses. It is fast and easy to use, enabling it to be used for car-service use also. CS machines are battery powered with 12V or 24V



GLOBALFLEX

## TECHNICAL DATA Crimping /hour: 100

Max crimping dia (mm)	g dia (mm) 10 - 87	
Max crimping dia (inches)	0.39 - 3.42	
Max crimping force (kN)	2000	
Max crimping force (tonnage)	200	
Cycle time 10mm (s)	7.2	
Hose size ID (inches)	2	
Die set series	P32	
Max opening (mm)	+33	
Max opening without dies (mm)	132	
Master die D/L (inches)	3.90/3.15	
Motor power (kW/HP)	21.1/3.05	
Oil tank volume (L)	4	



### Hydraulic Hose & Fittings

Looking for hydraulic hose and fittings to go with your new swaging machine? We stock large quantities of hydraulic hose and fittings for use across every industry including; 1 wire, 2 wire, 4 wire and 6 wire hose, and fittings available in mild or stainless steel.

### Looking to start a mobile hose replacement business?

We have a recommended starting stock list for any new van, speak to our sales team to discuss your specific needs.

30+ Years in the Hydraulic Industry
01472 255 928

Unit 3 Estate Road 5, South Humberside Industrial Estate, Grimsby, North East Lincs, DN31 2TG





#### P32 DIES \*Non standard dies

DieSetNo	Crimping Range	ID (mm)	L (mm)
P32/06*	6.0 - 8.0	6	25
P32/08*	8.0 - 10.0	8	25
P32/10*	10.0 - 12.0	10	55
P32/12*	12.0 - 14.0	12	55
P32/14*	14.0 - 16.0	14	55
P32/16	16.0 - 19.0	16	55
P32/19	19.0 - 22.0	19	55
P32/22	22.0 - 26.0	22	70
P32/26	26.0 - 30.0	26	70
P32/30	30.0 - 34.0	30	70
P32/34	34.0 - 45.0	34	75
P32/45	45.0 - 51.0	45	90
P32/51	51.0 - 57.0	51	90
P32/57	57.0 - 63.0	57	100
P32/63	63.0 - 69.0	63	100
P32/69	69.0 - 75.0	69	100
P32/74*	74.0 - 80.0	74	100
P32/78*	78.0 - 87.0	78	100