



Standard o-ring: NBR

Ball seat: POM  
(polyoxymethylene)

Part n°	DN	ØD1	R1	MAX. PRESSURE (bar)	HEX 1	A	B	C	D	E	H	I	K	L	V
<b>GB2V 6 L</b>	6	6L	M12x1.5	500	22	67	37	32	13	110	68	26	28	4,5	5
<b>GB2V 8 L</b>	6	8L	M14x1.5	500	22	67	37	32	13	110	68	26	28	4,5	5
<b>GB2V 10 L</b>	8	10L	M16x1.5	500	27	74	42	40	17	110	77	32	32	6,5	5
<b>GB2V 12 L</b>	10	12L	M18x1.5	500	27	74	42	40	17	110	77	32	32	6,5	5
<b>GB2V 15 L</b>	13	15L	M22x1.5	500	30	82	48	40	17	110	77	37,5	40	6,5	4,8
<b>GB2V 18 L</b>	13	18L	M26x1.5	400	30	82	48	40	17	110	77	37,5	40	6,5	4,8
<b>GB2V 22 L</b>	20	22L	M30x2	315	41	101	60	57	24	170	108	45	48	6,5	6,5
<b>GB2V 28 L</b>	25	28L	M36x2	315	50	108	65	64	28,5	170	115	55	57	6,7	6