



PIG'S TAIL RAIL



Part number	Size mm	Colour	Pack Qty. (Mtrs)	O.D. MM (Nominal)	I.D. MM (Nominal)	Wall Thickness MM	Band Width MM
RAIL 16-50	16	Grey	50	16	12.5	1.75	12
RAIL 20-50	20	Grey	50	20	16	2	14.5
RAIL 25-50	25	Grey	50	25	21	2	21
RAIL 32-50	32	Grey	50	32	27	2.5	24
RAIL 40 -50	40	Grey	50	40	34	3	30
RAIL 50-20	50	Grey	20	50	44	3	35

Pig's Tail® RAIL Protective Wrapping is a non-halogenic thermoplastic compound on a polypropylene base specifically developed for the RAIL industry. Meeting (V0) flame retardant requirements and certified according to EN 45545-2. In addition to high flame retardancy, it fulfills the fire protection requirements R22 and R23 for the hazard level HL2. Pig's Tail Rail also meets the ISO 4589-2 and ISO 5659-2 standards. This product also has an extremely good balance of mechanical properties.

Pig's Tail ® Protective Wrapping is designed to protect hydraulic and pneumatic hoses against impact and abrasion. Also suitable for protection of cables including fibreoptics either singular or bundled.

It is a heavy duty form of spiral protection suited to heavy industrial applications.

Made from High Density Polyethylene (HDPE).

Can be used for single hoses or multiple hose bundles.

Operating temperatures -50°C up to +120°C.

Suitable for use with all hydraulic fluids including glycol and phosphate ester based products.

Rounded edges for enhanced performance and safe handling.



PIG'S TAIL STANDARD



Part number	Size mm	Colour	Pack Qty. (Mtrs)
R9SSG-150	9	Yellow	150
R12SSG-50	12	Yellow, Red	50
R16SSG-20	16	Yellow, Red, Green, Blue	20
R20SSG-20	20	Yellow, Red, Green, Blue	20
R25SSG-20	25	Yellow, Red, Green, Blue	20
R32SSG-20	32	Yellow, Red, Green, Blue	20
R40SSG-20	40	Yellow, Red, Green, Blue	20
R50SSG-20	50	Yellow	20
R63SSG-20	63	Yellow	20
R75SSG-20	75	Yellow	20
R90SSG-20	90	Yellow	20
R110SSG-12	110	Yellow	12
R125SSG-12	125	Yellow	12
R140SSG-8	140	Yellow	8
R160SSG-6	160	Yellow	6