

Hydraulic hoses TrAle  
TrAle steel braid  
**2SCK hose**

Page: 1/1



**Composition:** ·Inner tube: special synthetic rubber resistant to hydraulic oil.  
·Reinforcement: two braids of steel wire.  
·Cover: synthetic rubber resistant to oil, abrasion and weather.

**Working temperature:** From -40° C to +100° C.

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MS2SCK04	1/4"	6.6	13,4	450	6.525	1.800	26.100	45	0.27
MS2SCK05	5/16"	8.3	15	420	6.090	1.680	24.360	60	0.31
MS2SCK06	3/8"	9.9	17	385	5.585	1.540	22.340	70	0.39
MS2SCK08	1/2"	13	20,7	345	5.000	1.380	20.000	90	0.52
MS2SCK10	5/8"	16.4	23,6	290	4.205	1.160	16.820	130	0.651
MS2SCK12	3/4"	19.5	27,7	280	4.060	1.120	16.240	160	0.52
MS2SCK16	1"	26	35,6	200	2.900	800	11.600	210	1.15