



Technical Data Sheet

Bondloc B7774 Belt Dressing

PRODUCT DESCRIPTION

B7774 effectively boosts the performance of "V", flat and round drive belts by reducing slippage, thereby extending belt life, reducing energy needs and the noise associated with slipping belts.

APPLICATIONS

B7774 can be used on all drive belts, such as "V", flat and round.

USEFUL NOTES

- Highly tacky product – effectively reduces slippage
- Suitable for all drive belts
- Increases belt life
- Boosts transmitted power by up to 50%
- Helps in the reduction of energy costs
- High adhesion prevents thrown off □
- Resistant to oxidation
- Easily removed.

INSTRUCTIONS FOR USE

Shake can well before use. Spray from 25-30cm ensuring an even coating over the whole surface. Slippage will decrease as product is distributed.

STORAGE

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

TECHNICAL FEATURES

Appearance	Clear tacky low viscosity fluid
Odour	Low odour after solvent has evaporated
Contents	Blend of synthetic polymer plasticiser, naphtha solvent and hydrocarbon propellants. No silicones.
Solubility	Insoluble in water
Storage	Below 50°C
Flash Point	-40°C
Relative Gravity	0.673
Temperature Range	Up to 130°C

HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

PACKAGING FORMAT

Aerosol Can.....500ml

Bondloc UK Ltd.
Units 1 & 2
Bewdley Business Park
Bewdley, Worcestershire
DY12 2TZ, UK

+44 (0) 1299 269 269
sales@bondloc.co.uk





Technical Data Sheet

Bondloc B7774 Belt Dressing

PRODUCT DISCLAIMER

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

Bondloc UK Ltd.
Units 1 & 2
Bewdley Business Park
Bewdley, Worcestershire
DY12 2TZ, UK

+44 (0) 1299 269 269
sales@bondloc.co.uk

