

Hydraulic hoses TrAle GOLD

Steel Braid TrAle GOLD - RockCover

EN 857 2SC hose TrAle Gold - RockCover



Composition:

- Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
- Reinforcement: two braids of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

Working temperature: From -40° C to +100° C.

FLAME RETARDANT according to ISO 8330: 2014

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Vacuum (bar)	Bending radius (mm)	Weight (kg/m)
ML2SC04RC	1/4"	6.6	13	400	5.800	1.600	23.200	-0.95	75	0.25
ML2SC06RC	3/8"	9.9	16,6	330	4.785	1.320	19.140	-0.95	90	0.37
ML2SC08RC	1/2"	13	20	275	3.990	1.100	15.950	-0.95	130	0.45
ML2SC10RC	5/8"	16.6	23,9	250	3.625	1.000	14.500	-0.8	170	0.61
ML2SC12RC	3/4"	19.5	27,6	215	3.120	860	12.470	-0.8	200	0.76
ML2SC16RC	1"	26	35,6	165	2.395	660	9.570	-0.8	250	1.15

