

Hydraulic hoses TrAle

TrAle Hydrowashing hose for hot water

Hot water superservice 2SC blue

Page: 1/1



Composition:

- Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
- Reinforcement: two braids of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

Working temperature: From -40° C to +155° C (peak).

| Part n° | DN | Ø in | Ø out | Working Pressure (bar) | Working pressure (psi) | Burst pressure (bar) | Burst pressure (psi) | Bending radius (mm) | Weight (kg/m) |
|----------|-------|------|-------|------------------------|------------------------|----------------------|----------------------|---------------------|---------------|
| MSC0214A | 1/4" | 6,5 | 13,9 | 400 | 5.800 | 1.600 | 23.200 | 75 | 0,19 |
| MSC0215A | 5/16" | 8,3 | 14,6 | 400 | 5.800 | 1.400 | 20.300 | 85 | 0,30 |
| MSC0216A | 3/8" | 9,9 | 16,6 | 400 | 5.800 | 1.320 | 19.140 | 90 | 0,37 |
| MSC0218A | 1/2" | 12,9 | 21 | 275 | 3.988 | 1.100 | 15.950 | 130 | 0,36 |