

CRIMPING MACHINES

OM-32

The OM-32 is an electrically operated workshop crimping machine designed to up to crimp up to 20 4 wire. Perfect for batch size hose assemblies it is quick, reliable and easy to use. Available in 1 phase and 3 phase (special voltages on request) and comes with an 12 off die set as standard.



SPECIFICATION

- Hose capacity 3/16" to 2" 4 wire
- Dial adjusted digital position indicator
- Available in 1phz or 3phz

- Twin return strut design
- Quick change system
- 12 off die set as standard.

TECHNICAL DATA				
Hose capacity:	3/16" - 2" (4 wire)			
Swaging ranges:	8mm - 82mm			
Voltages:	220/240 single phase 50/60hz - 380/440 three phase 50/60hz			
Radial swaging force:	2517 KN			
Max opening without dies:	124mm			
Max cycle time:	5 seconds closing 5 seconds opening			
Pump:	Twin speed 4600 psi			





CRIMPING MACHINES

OM-32

The OM-32 is an electrically operated workshop crimping machine designed to up to crimp up to 20 4 wire. Perfect for batch size hose assemblies it is quick, reliable and easy to use. Available in 1 phase and 3 phase (special voltages on request) and comes with an 12 off die set as standard.





DIE SET TABLE

Die Set	Range (mm)	Length (mm)	Max Ferrule Diameter (mm)	Die Set	Range (mm)	Length (mm)	Max Ferrule Diameter (mm)
08-32*	08.0 - 09.9	40.0	20.0	34-32	34.0 - 39.9	70.0	46.0
10-32*	10.0 - 11.9	40.0	22.0	40-32	40.0 - 45.9	70.0	52.0
12-32*	12.0 - 13.9	40.0	24.0	46-32	46.0 - 51.9	80.0	58.0
14-32*	14.0 - 15.9	40.0	26.0	52-32	52 - 57.9	80.0	64.0
16-32	16.0 - 18.9	40.0	28.0	58-32	58 - 63.9	80.0	70.0
19-32	19.0 - 21.9	40.0	31.0	64-32	64 - 69.9	80.0	66.0
22-32	22.0 - 25.9	50.0	34.0	70-32	70 - 82.0	95.0	82.0
26-32	26.0 - 27.9	50.0	38.0				
28-32*	28.0 - 29.9	50.0	40.0				
30-32	30.0 - 33.9	60.0	42.0				

^{*}Non standard dies

