

Industrial hoses INDUSTrAle

Food hoses

Alcoholic beverages max. 40% FDA 10 bar



Application: A flexible suction and discharge hose for use in breweries, as well as in the food and beverage industries.
Suitable for use with alcohol (max.40%) and soft drinks, as well with fatty (max. 36%) and non-fatty foods.

Composition: Tube: EPDM, white, smooth, food quality.
Reinforcement: Textile, wrapped, zinc plated steel wire helix
Cover: SBR/NR/EPDM, red, abrasion resistant, ozone and weather resistant, cloth impression

Temperature range: -35°C / +95°C. Steam cleaning up to 130°C / max. 30 min, unpressurized

Safety factor: 3,15 : 1

Norm / Registration: BfR XXI:2002 (Kat.2), FDA (CFR 21 § 177.2600)

Part n°	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MI020610025	25	37	10	145	31,5	455	110	0,95
MI020610038	38	50	10	145	31,5	455	180	1,37
MI020610051	51	63	10	145	31,5	455	250	2,02
MI020610076	76	88	10	145	31,5	455	450	3,39