



**Composition:**

- Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
- Reinforcement: two braids of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

**Working temperature:** From -40° C to +100° C.

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Vacuum (bar)	Bending radius (mm)	Weight (kg/m)
<b>M2SC04</b>	1/4"	6,6	13	400	5.800	1.600	23.200	-0,95	75	0,25
<b>M2SC05</b>	5/16"	8,3	14,6	350	5.075	1.400	22.050	-0,95	85	0,30
<b>M2SC06</b>	3/8"	9,9	16,6	330	4.785	1.320	19.140	-0,95	90	0,37
<b>M2SC08</b>	1/2"	13	20	275	3.990	1.100	15.950	-0,95	130	0,45
<b>M2SC12</b>	3/4"	19,5	27,6	215	3.120	860	12.470	-0,80	200	0,76
<b>MDD2SC04</b>	1/4"	6,6	13	400	5.800	1.600	23.200	-0,95	75	0,25
<b>MDD2SC05</b>	5/16"	8,3	14,6	350	5.075	1.400	22.050	-0,95	85	0,30
<b>MDD2SC06</b>	3/8"	9,9	16,6	330	4.785	1.320	19.140	-0,95	90	0,37
<b>MDD2SC08</b>	1/2"	13,0	20,2	275	3.990	1.100	15.950	-0,95	130	0,45
<b>MDD2SC10</b>	5/8"	16,4	23,9	250	3.625	1.000	14.500	-0,80	170	0,61
<b>MDD2SC12</b>	3/4"	19,5	27,6	215	3.120	860	12.470	-0,80	200	0,76
<b>MDD2SC16</b>	1"	26,0	35,6	165	2.395	660	9.570	-0,80	250	1,15