



**Composition:**

- Inner tube: synthetic rubber resistant to hydraulic, mineral and vegetable oil.
- Reinforcement: one braid of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

**Working temperature:** From -40° C to +155° C (peak).

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
<b>MSC0114A</b>	1/4"	6,5	13,2	225	3.263	900	13.050	75	0,12
<b>MSC0115A</b>	5/16"	8,1	14,2	215	3.118	860	12.470	85	0,14
<b>MSC0116A</b>	3/8"	9,7	16	180	2.610	720	10.440	90	0,19
<b>MSC0118A</b>	1/2"	12,9	19,2	160	2.320	640	9.280	130	0,22
<b>MDDSC0114A</b>	1/4"	6,5	13,2	225	3.263	900	13.050	75	0,12
<b>MDDSC0115A</b>	5/16"	8,1	14,2	215	3.118	860	12.470	85	0,14
<b>MDDSC0116A</b>	3/8"	9,7	16	180	2.610	720	10.440	90	0,19
<b>MDDSC0118A</b>	1/2"	12,9	19,2	160	2.320	640	9.280	130	0,22