

TEXAS 10 S&D

10 BAR OIL SUCTION AND DELIVERY




Order Ref: OSH-SIZE MM

Tube: Oil and petrol resistant, conductive synthetic nitrile black rubber.

Reinforcement: High tensile synthetic textile, steel wire helix and anti-static copper wire.

Cover: Oil, weather, ozone, abrasion and sea water resistant, special synthetic rubber.

Application: Suction & delivery for filling and discharging tanks, petrol tankers and ships with unleaded fuels (EN228:2017) with an aromatic content of components 50% max.



(+100°C when used with oil)

INTERNAL DIAMETER		OUTER DIAMETER	WORKING PRESSURE		BURSTING PRESSURE		VACUUM	BEND RADIUS	HOSE WEIGHT	COIL LENGTH
inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/m	m
3/4	19	30	10	145	30	450	-0.92	90	600	10/20/30/40
1	25.4	35	10	145	30	450	-0.92	110	650	10/20/30/40
1 1/4	32	42	10	145	30	450	-0.92	140	835	10/20/30/40
1 1/2	38	48	10	145	30	450	-0.92	170	1050	10/20/30/40
1 3/4	44.5	55	10	145	30	450	-0.92	210	1290	10/20/40
2	50.8	61	10	145	30	450	-0.92	250	1495	10/20/40/61
2 1/4	57	69	10	145	30	450	-0.92	275	1885	10/20/40
2 3/8	60	72	10	145	30	450	-0.92	295	1990	10/20/40
2 1/2	63.5	74	10	145	30	450	-0.92	310	2010	10/40
3	76.2	87	10	145	30	450	-0.92	380	2337	10/40
3 1/2	90	102	10	145	30	450	-0.92	450	2940	10/20/40
4	101.6	115	10	145	30	450	-0.92	510	3440	10/20/30/40
4 1/2	115	132	10	145	30	450	-0.92	475	5100	10/20
5	127	145	10	145	30	450	-0.92	650	6195	10/20